

# DECORVAL

## Decorative water paint

### DESCRIPTION

Semi-opaque water paint for foot-traffic areas. It is suitable to protect and improve the appearance of bituminous conglomerate or cement pavements such as: tennis courts, field tracks, alleys and sidewalks.

### CHARACTERISTICS

**Specific weight:** 1,35

**Min. temperature of application:** +10°C

DECORVAL forms an abrasion-resistant film; its elasticity allows the dried film to adapt to any dilatation movements of the deck caused by temperature range. It has a very high coating capacity.

**WATER PAINT CLASSIFIED AS NON-TOXIC AND NON-HARMFUL**

### APPLICATION

The first coat has to be thinned with 20% water; for the last coat, according to the application type, use the product pure or diluted with max. 10% water.

Best covering capacity: 500 ÷ 600 gr/m<sup>2</sup>

### COLOURS

Red, green, white.

### PRECAUTIONS AND APPLICATION METHODS

Prevent freezing of the product and do not expose to temperatures below +5°C. Stir carefully before use. Apply DECORVAL on compact surfaces free from oil stains, dust or crumbly parts. There must be no drooped spots on the surface and an adequate slope to allow fast water drainage. The pavements carried out with bituminous conglomerates will need at least 15 days of oxidation since the bitumen's oily portion, which sets on the surface during the first days, could jeopardize the outcome of the painting. Before painting, cement pavements must be completely matured and properly pretreated with VERVAL PRIMER TRASPARENTE (100 / 200 gr/m<sup>2</sup>). Clean the tools with water soon after use. DECORVAL can be applied by brush, roller or sprayer.

### PACKAGING

DECORVAL is available in 25 kg drums.

Rev. 1 - 10/08