

# Adesival Super PL

**Description** High performance adhesive bitumen membrane for roofing and waterproofing works. This product is designed as base layer for 2-layers roofing system or single layer for foundation walls.

**CE** Base layer for multi-layer roofing systems according with EN13707 for flat roofs. Layer for foundation waterproofing works according with EN13969.

**Field of use** Exposed not-accessible roofs, technical roofs exposed or under heavy protection. Foundation walls.

**Certifications and Agreements** CE marking - FPC certificate number 1370-CPR-0042

**Composition**  
**Top Surface:** Film or PP-non woven  
**Back Surface:** Removable Film  
**Reinforcement:** Polyester reinforced with fiber glass

**Method of application** Self-adhesive

Dimension and packaging	Adesival Super	2PL	3PL	4PL
Thickness (mm)		2,0	3,0	4,0
Weight (kg/m2)		-	-	-
Rolls (m)		1x15	1x10	1x10



Property	Test Method	Unit	Value	Tolerance
Lenght	EN 1848-1	m	10 / 15	-1%
Width	EN 1848-1	m	1,0	-1%
Thickness	EN 1849-1	mm	2,0 / 3,0 / 4,0	±0,2
Weight	EN 1849-1	Kg/m2	NPD	-
Tensile strength at max	EN 12 311-1	L x T (N/50mm)	550/400	-20%
Elongation at max	EN 12 311-1 1999	L x T (%)	40/40	-15
Nail tearing resistance	EN 12 310-1	L x T (N)	150/150	-30%
Static load	EN 12 730	Kg	15	≥
Resistance to impact	EN 12691	mm	900	≥
Flexibility at low temperature	EN 1109	(°C)	-25	≤
Flow resistance at elevated temperature	EN 1110	(°C)	100	≥
Flow resistance at elevated Temperature after thermal ageing	EN1296 EN 1110	(°C)	NPD	-
Dimensional stability	EN 1107-1	%	±0,3	≤
Watertightness	EN 1928-B	kPa	60	≥
Vapour Transmission (μ)	EN 1931	-	20000	≥
Reaction to fire	EN 13501-1	-	F	-
External fire performance	EN 13501-5	-	Froof	-

#### Storage

This product is packaged in rolls set up vertically on pallet or wooden box. It must be stored vertically under shelter, away from heat sources.

#### Modifications

Our company reserves the right to modify its composition as a result of technologic and experiments improvements. This product data sheet supersedes the previous edition, to obtain the updated technical data sheet, please contact our technical department.