

# Adesival Vap BE

**Description** Adhesive bitumen Vapour barrier membrane for roofing works.

**CE** Vapour barrier according with EN13970

**Field of use** Insulated flat roofs

**Certifications and Agreements** CE marking - FPC certificate number 1370-CPR-0042.

**Composition**  
**Top Surface:** Removable siliconised Film  
**Back Surface:** Removable siliconised Film  
**Reinforcement:** Polyester with aluminium foil

**Method of application** Self-adhesive

<b>Dimension and packaging</b>	<b>Adesival Vap BE</b>	<b>2</b>	<b>3</b>
Thickness (mm)		2,0	3,0
Weight (kg/m2)		-	-
Rolls (m)		1x15	1X10



Property	Test Method	Unit	Value	Tolerance
Lenght	EN 1848-1	m	15 / 10	-1%
Width	EN 1848-1	m	1,0	-1%
Thickness	EN 1849-1	mm	2,0 / 3,0	±0,2
Weight	EN 1849-1	Kg/m2	NPD	±10%
Tensile strength at max	EN 12 311-1	L x T (N/50mm)	350/200	-20%
Elongation at max	EN 12 311-1 1999	L x T (%)	20/20	-15
Nail tearing resistance	EN 12 310-1	L x T (N)	110/100	-30%
Static load	EN 12 730	Kg	NPD	≥
Resistance to impact	EN 12691	mm	700	≥
Flexibility at low temperature	EN 1109	(°C)	-10	≤
Flow resistance at elevated temperature	EN 1110	(°C)	NPD	≥
Watertightness	EN 1928-B	kPa	60	≥
Vapour Transmission (μ)	EN 1931	-	1500000	≥
Sd value	EN 1931	m	2700	≥

#### Storage

This product is packaged in rolls set up vertically on pallet or wooden box. It must be stored vertically under shelter, away from heat sources.

#### Modifications

Our company reserves the right to modify its composition as a result of technologic and experiments improvements. This product data sheet supersedes the previous edition, to obtain the updated technical data sheet, please contact our technical department.